

**Miracle<sup>®</sup>**

**Future Business LLC.**



**Part# LD117A Miracle 10" LCD Monitor**

**LD117A Black**

**MIRACLE 10.4" LCD XGA 1024 x 768**

<b>LCD Display</b>	10.4" TFT LCD, Anti-glare, Hard coating (3H)
<b>Signal input</b>	Video: RGB Analog; Sync.: TTL
<b>Response Time</b>	40ms
<b>Dot Pitch</b>	0.2055 (H) x 0.2055 (V) mm
<b>Resolution</b>	VGA 640 x 480 (60/72/75); SVGA 800 x 600 (56/60/72/75); XGA 1024 x 768 (43/60/72/75)
<b>Contrast Ratio</b>	300 : 1 (typical)
<b>Brightness</b>	150 cd/m <sup>2</sup> (typical)
<b>Display color</b>	262K colors
<b>Viewing Angle</b>	L/R: +80°~ -80° (typical); U/D: +80°~ -80° (typical)
<b>Display Size</b>	210.4(H)mm x 157.8(V)mm
<b>Speaker</b>	0.7W per channel
<b>Power Source</b>	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/2.0A
<b>Power Consumption</b>	<20W
<b>EPA VESA</b>	On, Off, Suspend, Stand by
<b>User Controls</b>	Power on/off with LED, OSD Menu/Select, Adjustment +/-
<b>Input Connector</b>	15 pin D-type signal cable
<b>Operating Temperature</b>	5°C ~ 40°C
<b>Operating Humidity</b>	5% ~ 90%
<b>Dimension</b>	11"W x 5"D x 11"H (without base 11" W x 2" D x 9" H)
<b>Weight</b>	6 lbs (3 lbs without stand)
<b>Wall mount</b>	VESA standard 75 x 75 mm
<b>Certification</b>	FCC, UL, cUL, CCC