

Miracle®**Future Business LLC.****Part# LT08B Miracle 8" LCD Monitor****LT08B Black****MIRACLE 8.0" LCD SVGA 800 x 600**

LCD Display	8.0" TFT LCD, Active Matrix Panel
Signal input	Video: RGB Analog 0.7V (Peak to Peak); Sync.: TTL (Positive or Negative)
Response Time	25ms
Dot Pitch	0.2025 (H) x 0.2025 (V) mm
Resolution	VGA 720 x 400 (70); 640 x 480 (60/72/); SVGA 800 x 600 (60/72/75);
Contrast Ratio	500 : 1
Brightness	250 cd/m ² ; Twin CCFLs, Long life backlight (MTBF 50000hrs)
Display color	16M colors
Viewing Angle	L/R: +70°~ -70° U/D: +50°~ -60°
Display Size	162(H)mm x 121.5(V)mm
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/1.5A
Power Consumption	<16W;
EPA VESA	On, Off, Suspend, Stand by
User Controls	Power on/off with LED, OSD Menu/Select, Auto/Select, Adjustment +/-
Input Connector	15 pin D-type signal cable
Operating Temp./Humidity	5°C ~ 40°C / 20% ~ 80% (no condensation); Altitude to 10,000 feet
Storage Temp./Humidity	-20°C ~ 60°C / 10% ~ 90% (no condensation)
Dimension	8¼"W x 5"D x 8"H (without base 8¼" W x 1½" D x 6¾" H)
Weight	Net 2.6 lbs (4 lbs with packing)
Wall mount	VESA standard 75 x 75 mm
Certification	FCC, CCC
Touch screen	Option