

**Miracle®**

**Future Business LLC.**



**Part# LT10W Miracle 10" LCD Monitor**

<b>LT10W White</b>	<b>MIRACLE 10.4" LCD SVGA 800 x 600</b>
<b>LCD Display</b>	10.4" TFT LCD, Active Matrix Panel
<b>Signal input</b>	Video: RGB Analog 0.7V (Peak to Peak); Sync.: TTL (Positive or Negative)
<b>Response Time</b>	25ms
<b>Dot Pitch</b>	0.264 (H) x 0.264 (V) mm
<b>Resolution</b>	VGA 640 x 350 (70); 720 x 400 (70); 640 x 480 (60/72/75); SVGA 800 x 600 (56/60/72/75);
<b>Contrast Ratio</b>	300 : 1
<b>Brightness</b>	350 cd/m <sup>2</sup> /font>
<b>Display color</b>	262K colors
<b>Viewing Angle</b>	L/R: +60° ~ -60° U/D: +40° ~ -40°
<b>Display Size</b>	211(H)mm x 158(V)mm
<b>Speaker</b>	0.7W per channel
<b>Power Source</b>	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/2.0A
<b>Power Consumption</b>	16W; stand by <5W
<b>EPA VESA</b>	On, Off, Suspend, Stand by
<b>User Controls</b>	Power on/off with LED, OSD Menu/Select, Auto/Select, Adjustment +/-
<b>Input Connector</b>	15 pin D-type signal cable
<b>Operating Temp./Humidity</b>	5°C ~ 40°C / 20% ~ 80% (no condensation); Altitude to 10,000 feet
<b>Storage Temp./Humidity</b>	-20°C ~ 60°C / 10% ~ 90% (no condensation)
<b>Dimension</b>	11"W x 5"D x 11"H (without base 11"W x 2"D x 9"H)
<b>Weight</b>	5.6 lbs (3 lbs without stand)
<b>Wall mount</b>	VESA standard 75 x 75 mm
<b>Certification</b>	FCC, CCC
<b>Touch screen</b>	Option