



Part# LT15A Miracle 15" LCD Monitor

LT15A Black	MIRACLE 15.1" LCD Monitor
LCD Display	15.1" active matrix TFT LCD
Signal input	Video: RGB Analog 0.7V; Sync.: TTL Positive or Negative
Scanning Frequency	Horizontal 18 ~ 60 KHz ; Vertical 56 ~ 75 Hz
Display Size	304 (H) x 228 (V) mm
Dot Pitch	0.297 (H) x 0.297 (V) mm
Max. Resolution	XGA 1024 x 768 (60/72/75Hz)
Contrast Ratio	500 : 1 (typical)
Brightness	250 cd/m ² ; (typical)
ResponseTime	8ms
Display color	16M
Viewing Angle	L/R: +75° ~ -75°(typical); U/D: +70° ~ -60°(typical)
Speaker	Stereo 0.7W x 2
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/4.0Am
Power Consumption	30W
User Controls	Auto configuration, Power on-off push switch, brightness, Contrast, V-size, H-phase, Color, Language, Volume, Phase, Clock adjustment
Input Connector	15 pin D-type; DVI
Operating Temperature	5°C ~ 35°C
Storage Temperature	-20°C ~ +60°C
Operating Humidity	20% ~ 80%
Storage Humidity	10% ~ 90%
Dimension	14¾" W x 7½" D x 14" H
Weight (net)	6 lbs
Certification	FCC, CE