



Part# LT15K Miracle 15" LCD Monitor

LT15K	MIRACLE 15" LCD Monitor
LCD Display	15" TFT LCD Panel
Signal input	Video: RGB Analog 0.7V; Sync.: TTL positive or negative;
Display Mode	VGA 720x400 (70Hz); 640x480 (60/72/75Hz); SVGA 800x600 (60/72/75Hz); XGA 1024x768 (60/72/75Hz)
Dot Pitch	0.297 (H) x 0.297 (V) mm
Max. Resolution	XGA 1024 x 768
Contrast Ratio	500 : 1 (typical)
Brightness	250 cd/m ² ; (typical)
Display color	16M
Viewing Angle	L/R: +75° ~ -75°(typical); U/D: +70° ~ -60°(typical)
Response	8ms
Speaker	Stereo 0.7W x 2
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V
Power Consumption	<30W
Front Controls	Auto, Power, Menu, Up/+, Down/-
Input Connector	15 pin D-type signal cable, DVI-D Single Link
Wall Mount	VESA 100 x 100
Operating Temperature, Humidity	0°C ~ 40°C, 20% ~ 80%
Storage Temperature, Humidity	-20°C ~ 60°C, 10% ~ 90%
Dimension	14¾"W x 14"H x 7½" D
Weight	8.5 lbs (11 lbs with packing)
Certification	FCC, CE, CCC,