



Part# LT17B-IU Miracle 17" Infrared Touch Monitor

LT17B-IU	MIRACLE 17" Infrared Touch LCD
LCD Display	17" TFT Active Matrix Panel
Signal input	Video: R.G.B. Analog 0.7V; Sync.: TTL positive or negative
Display Mode	VGA 640x350(70Hz);VGA 720x400(70Hz); 640x480(60/72/75Hz); SVGA 800x600(56/60/72/75Hz); XGA 1024x768(60/70/75Hz); SXGA 1280x1024(60/75Hz)
Dot Pitch	0.264 (H) x 0.264 (V) mm
Max. Resolution	SXGA 1280 x 1024
Contrast Ratio	350 : 1
Brightness	250 cd/m ²
Display color	16M
Viewing Angle	L/R: +80° ~ -80°; U/D: +80° ~ -80°
Response	35ms
Speaker	1W / Per Channel
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/5.0A
Power Consumption	<30W
Front Controls	Power Switch, Menu/Select (up, down), Adjust (+,-)
Input Connector	15 pin D-Sub
Wall Mount	N/A
Operating Temperature,Humidity	5°C ~ 35°C, 20% ~ 80%
Storage Temperature,Humidity	-20°C ~ 60°C, 10% ~ 90%
Dimension	450mmW x 437mmH x 195mm D
Weight	5.9Kg
Certification	FCC, CE, CCC,