



Part# LT19BV Miracle 19" VGA/Video Monitor

Features:

- 19" TFT LCD
- Input: DB15 (VGA), Video, 1 BNC, 1 Audio
- Output: 1 BNC
- Small base + Wall mountable, buttons on bottom
- A+ panel, fire resistant material cases

Specifications	
LCD Display	19" TFT LCD Panel
Display Size	376.3(H)x301.0(V)mm
Pixel Pitch	0.297(H)x0.294(V)mm
Display Mode	VGA 720x400(70Hz) VGA 640x480(60/72/75 Hz) SGVA 800x600(60/72/75 Hz) SXGA 1280x1024(60/72/75 Hz)
Max Resolution	SXGA 1280x1024
Display Color	16M
Contrast Rate	800:1
Brightness	300 Cd/m ²
Response Time	5ms
View Angle(CR>10)	+80 ~ -80° (U/D) +80 ~ -80°(L/R)
Input Signal	R.G.B. Analog 0.7V
Signal Connector	Video VGA PAL/NTSC
Front Control	DB15, Video, 1 BNC, 1 Audio Power, Menu, Auto, Up/+, Down/- "Color", "OSD", "Sound"
Plug & Play	DDC1/2B
Audio System (optional)	1W/Per Channel
Power Adapter	Input AC 100-240V, 50-60Hz, Output DC 12V/4.0A
Operating Conditions	Temperature Humidity 5° C~35° C (41° F~95 °F) 20%~80%
Storage Conditions	Temperature Humidity -20° C ~ 60° C(-4° F~140 °F) 10% ~90%
Dimensions (WxHxD)	425x410x150mm
Weight (Net)	3.8 Kg
Regulations	FCC, CE

Specifications are subject to change without notice.



back



Connectors



side

Options:

10" 12" 15" 19" VGA/Video Monitors